

DOCUMENT NO: TM-104	TITLE: Test Method for Measurement of Diaphragm Neck I.D.	PAGE: 1 of 2
APPLICATION:	REVISION: 1/6/08	DATE: 1/6/08

PURPOSE: The test methods outlined in this document define equipment and techniques for measuring the Neck I.D. of loudspeaker diaphragms.

SCOPE: This document is intended to be used in conjunction with the applicable ALMA International document(s) in which it is referenced. These referencing document(s) may contain general information not included in this document, but which applies to this document, thus it is not recommended to use this document outside of its intended context. In the event of conflict, information in this document supercedes information in the referencing document(s).

RESPONSIBILITY: ALMA International Component Standards Sub-Committee

RECORDS: This document will be maintained and kept on file by ALMA International. Measurement results shall be maintained by the entity performing the measurement.

RELATED DOCUMENTS:

ALMA International Nomenclature Prints (NP's)

ALMA International Dimensioning and Tolerancing Guidelines (DG's)

ALMA International Measurement Guidelines (MG's)

1 Introduction

The test methods outlined in this document define equipment and techniques for measuring the Neck I.D. of loudspeaker diaphragms (cones).

2 Required Equipment

- Tapered Gauge
- Dial or Digital Caliper

3 Method

- 3.1 Select a taper gauge, which has a diameter range that will accept the specified Neck I.D. range.
- 3.2 Insert the taper gauge from the bottom (underside) of the cone.
- 3.3 Hold the taper gauge upward and shake it lightly until the cone comes to a rest. Position the cone further on the gauge by raising the lowest point of the cone neck to a level position with the highest point of the cone neck where it comes into contact with the gauge, then shake the gauge lightly to settle. Repeat this process as necessary until the cone neck is at its lowest point on the gauge without being forced.
- 3.4 Take the caliper and measure the outer diameter of the gauge at the point where the lowest point of the cone neck comes into contact with it.

DOCUMENT NO: TM-104	TITLE: Test Method for Measurement of Diaphragm Neck I.D.	PAGE: 2 of 2
APPLICATION:	REVISION: 1/6/08	DATE: 1/6/08

4 GR&R (Gage Repeatability and Reproducibility)

0.10 mm, typically.

Revision History

Rev Level	Description of Change	Prepared/ Changed By/ Date	Approved By/ Date
DRAFT	Create document	George Wise 7/18/02	
1/6/08	Updated format and nomenclature, added GR&R information	Brian Sterling 1/5/07	ALMA Committee 1/6/08